

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Cancelled)

2. (Currently Amended) A telecommunications network having a first entity which communicates with a second entity by sending a packet having a compressed header, characterized in that the first entity also sends to the second entity a header compression key associated with the packet, the header compression key having a first field which is utilized for distinguishing between different flows of compressed packets, wherein a first subset of values for the first field of the header compression key is employed to distinguish between different header compression identifiers and wherein a second subset of values for the first field is employed to distinguish between the different flows of compressed packets.

3. (Original) The apparatus of claim 2, wherein the values of the second subset succeed the values of the first subset.

4. (Original) The apparatus of claim 2, wherein the header compression identifiers denote a header compression method and a packet type.

5. (Original) The apparatus of claim 2, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

6. (Original) The apparatus of claim 5, wherein the header compression key is a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

7. (Original) The apparatus of claim 2, wherein the second set of values comprise context identifiers for a compression/decompression algorithm.

8. (Original) The apparatus of claim 2, wherein the second set of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

9. (Original) The apparatus of claim 8, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

10. (Cancelled)

11. (Currently Amended) A telecommunications network having a first entity which communicates with a second entity by sending a packet having a compressed header, characterized in that the first entity also sends to the second entity a header compression key associated with the packet, the header compression key having a first field which is utilized for distinguishing between different flows of compressed packets, wherein the header compression key has a second field which is utilized to indicate whether the first field of the header compression key is utilized exclusively for distinguishing between the different flows of compressed packets.

12. (Original) The apparatus of claim 11, wherein a first value in the second field of the header compression key indicates that the first field of the header compression key is utilized exclusively for distinguishing between the different flows of compressed packets, and wherein a second value in the second field of the header compression key indicates that data in the first field of the header compression key, depending on its value, can be either a header compression identifier or a packet flow identifier.

13. (Original) The apparatus of claim 12, wherein the data in the first field of the header compression key, when included in a first subset of values, distinguishes between different header compression identifiers, and wherein the data in the first field of the

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

header compression key, when included in a second subset of values, distinguishes between the different flows of compressed packets.

14. (Original) The apparatus of claim 13, wherein the values of the second subset succeed the values of the first subset.

15. (Original) The apparatus of claim 13, wherein the header compression identifiers denote a header compression method and a packet type.

16. (Original) The apparatus of claim 13, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

17. (Original) The apparatus of claim 16, wherein the header compression key is included in a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

18. (Currently Amended) The apparatus of claim 13, wherein the second subset of values comprise context identifiers for a compression/decompression algorithm.

19. (Currently Amended) The apparatus of claim 18, wherein the second subset of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

20. (Original) The apparatus of claim 19, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

21. (Original) The apparatus of claim 11, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

22. (Original) The apparatus of claim 21, wherein the header compression key is included in a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the second field is a PDU type field.

23. (Original) The apparatus of claim 11, wherein the header compression key is included in a protocol data unit of a link layer protocol.

24. (Cancelled)

25. (Cancelled)

26. (Cancelled)

27. (Cancelled)

28. (Currently Amended) A node of a cellular telecommunications network which has a first entity which communicates with a second entity by sending a packet having a compressed header, characterized in that the first entity also sends to the second entity a header compression key associated with the packet, the header compression key having a first field which is utilized for distinguishing between different flows of compressed packets, wherein a first subset of values for the first field of the header compression key is employed to distinguish between different header compression identifiers and wherein a second subset of values for the first field is employed to distinguish between the different flows of compressed packets.

29. (Original) The apparatus of claim 28, wherein the values of the second subset succeed the values of the first subset.

30. (Original) The apparatus of claim 28, wherein the header compression identifiers denote a header compression method and a packet type.

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

31. (Original) The apparatus of claim 28, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

32. (Original) The apparatus of claim 31, wherein the header compression key is a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

33. (Original) The apparatus of claim 28, wherein the second set of values comprise context identifiers for a compression/decompression algorithm.

34. (Original) The apparatus of claim 28, wherein the second set of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

35. (Original) The apparatus of claim 34, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

36. (Cancelled)

37. (Currently Amended) A node of a cellular telecommunications network which has a first entity which communicates with a second entity by sending a packet having a compressed header, characterized in that the first entity also sends to the second entity a header compression key associated with the packet, the header compression key having a first field which is utilized for distinguishing between different flows of compressed packets, wherein the header compression key has a second field which is utilized to indicate whether the first field of the header compression key is utilized exclusively for distinguishing between the different flows of compressed packets.

38. (Original) The apparatus of claim 37, wherein a first value in the second field of the header compression key indicates that the first field of the header compression key is utilized exclusively for distinguishing between the different flows of compressed

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

packets, and wherein a second value in the second field of the header compression key indicates that data in the first field of the header compression key, depending on its value, can be either a header compression identifier or a packet flow identifier.

39. (Original) The apparatus of claim 38, wherein the data in the first field of the header compression key, when included in a first subset of values, distinguishes between different header compression identifiers, and wherein the data in the first field of the header compression key, when included in a second subset of values, distinguishes between the different flows of compressed packets.

40. (Original) The apparatus of claim 39, wherein the values of the second subset succeed the values of the first subset.

41. (Original) The apparatus of claim 39, wherein the header compression identifiers denote a header compression method and a packet type.

42. (Original) The apparatus of claim 39, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

43. (Original) The apparatus of claim 42, wherein the header compression key is included in a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

44. (Currently Amended) The apparatus of claim 39, wherein the second subset of values comprise context identifiers for a compression/decompression algorithm.

45. (Currently Amended) The apparatus of claim 44, wherein the second subset of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

46. (Original) The apparatus of claim 45, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

47. (Original) The apparatus of claim 37, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

48. (Original) The apparatus of claim 47, wherein the header compression key is included in a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the second field is a PDU type field.

49. (Original) The apparatus of claim 37, wherein the header compression key is included in a protocol data unit of a link layer protocol.

50. (Cancelled)

51. (Cancelled)

52. (Cancelled)

53. (Cancelled)

54. (Currently Amended) A user equipment unit (UE) having a first entity which communicates with a second entity by sending a packet having a compressed header, the second entity being situated at a node of a cellular telecommunications network, characterized in that the first entity also sends to the second entity a header compression key associated with the packet, the header compression key having a first field which is utilized for distinguishing between different flows of compressed packets, wherein a first subset of values for the first field of the header compression key is employed to distinguish between different header compression identifiers and wherein a second subset of values for the first field is employed to distinguish between the different flows of compressed packets.

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

55. (Original) The apparatus of claim 54, wherein the values of the second subset succeed the values of the first subset.

56. (Original) The apparatus of claim 54, wherein the header compression identifiers denote a header compression method and a packet type.

57. (Original) The apparatus of claim 54, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

58. (Original) The apparatus of claim 57, wherein the header compression key is a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

59. (Original) The apparatus of claim 54, wherein the second set of values comprise context identifiers for a compression/decompression algorithm.

60. (Original) The apparatus of claim 54, wherein the second set of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

61. (Original) The apparatus of claim 60, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

62. (Cancelled)

63. (Currently Amended) A user equipment unit (UE) having a first entity which communicates with a second entity by sending a packet having a compressed header, the second entity being situated at a node of a cellular telecommunications network, characterized in that the first entity also sends to the second entity a header compression key associated with the packet, the header compression key having a first field which is

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

utilized for distinguishing between different flows of compressed packets, wherein the header compression key has a second field which is utilized to indicate whether the first field of the header compression key is utilized exclusively for distinguishing between the different flows of compressed packets.

64. (Original) The apparatus of claim 63, wherein a first value in the second field of the header compression key indicates that the first field of the header compression key is utilized exclusively for distinguishing between the different flows of compressed packets, and wherein a second value in the second field of the header compression key indicates that data in the first field of the header compression key, depending on its value, can be either a header compression identifier or a packet flow identifier.

65. (Original) The apparatus of claim 64, wherein the data in the first field of the header compression key, when included in a first subset of values, distinguishes between different header compression identifiers, and wherein the data in the first field of the header compression key, when included in a second subset of values, distinguishes between the different flows of compressed packets.

66. (Original) The apparatus of claim 65, wherein the values of the second subset succeed the values of the first subset.

67. (Original) The apparatus of claim 65, wherein the header compression identifiers denote a header compression method and a packet type.

68. (Original) The apparatus of claim 65, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

69. (Original) The apparatus of claim 68, wherein the header compression key is included in a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

70. (Currently Amended) The apparatus of claim 65, wherein the second subset of values comprise context identifiers for a compression/decompression algorithm.

71. (Currently Amended) The apparatus of claim 70, wherein the second subset of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

72. (Original) The apparatus of claim 71, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

73. (Original) The apparatus of claim 63, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

74. (Original) The apparatus of claim 73, wherein the header compression key is included in a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the second field is a PDU type field.

75. (Original) The apparatus of claim 63, wherein the header compression key is included in a protocol data unit of a link layer protocol.

76. (Cancelled)

77. (Cancelled)

78. (Cancelled)

79. (Cancelled)

80. (Currently Amended) A method of operating a telecommunications network having a first entity which communicates with a second entity by sending a packet having a compressed header, the method characterized by sending from the first entity sends to

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

the second entity a header compression key associated with the packet, the header compression key having a first field which is utilized for distinguishing between different flows of compressed packets, wherein a first subset of values for the first field of the header compression key is employed to distinguish between different header compression identifiers and wherein a second subset of values for the first field is employed to distinguish between the different flows of compressed packets.

81. (Original) The method of claim 80, wherein the values of the second subset succeed the values of the first subset.

82. (Original) The method of claim 80, wherein the header compression identifiers denote a header compression method and a packet type.

83. (Original) The method of claim 80, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

84. (Original) The method of claim 83, wherein the header compression key is a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

85. (Original) The method of claim 80, wherein the second set of values comprise context identifiers for a compression/decompression algorithm.

86. (Original) The method of claim 80, wherein the second set of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

87. (Original) The method of claim 86, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

88. (Cancelled)

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

89. (Currently Amended) A method of operating a telecommunications network having a first entity which communicates with a second entity by sending a packet having a compressed header, the method characterized by sending from the first entity to the second entity a header compression key associated with the packet, the header compression key having a first field which is utilized for distinguishing between different flows of compressed packets, wherein the header compression key has a second field which is utilized to indicate whether the first field of the header compression key is utilized exclusively for distinguishing between the different flows of compressed packets.

90. (Original) The method of claim 89, wherein a first value in the second field of the header compression key indicates that the first field of the header compression key is utilized exclusively for distinguishing between the different flows of compressed packets, and wherein a second value in the second field of the header compression key indicates that data in the first field of the header compression key, depending on its value, can be either a header compression identifier or a packet flow identifier.

91. (Original) The method of claim 90, wherein the data in the first field of the header compression key, when included in a first subset of values, distinguishes between different header compression identifiers, and wherein the data in the first field of the header compression key, when included in a second subset of values, distinguishes between the different flows of compressed packets.

92. (Original) The method of claim 91, wherein the values of the second subset succeed the values of the first subset.

93. (Original) The method of claim 91, wherein the header compression identifiers denote a header compression method and a packet type.

94. (Original) The method of claim 91, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

95. (Original) The method of claim 94, wherein the header compression key is included in a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

96. (Currently Amended) The method of claim 91, wherein the second subset of values comprise context identifiers for a compression/decompression algorithm.

97. (Currently Amended) The method of claim 96, wherein the second subset of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

98. (Original) The method of claim 97, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

99. (Original) The method of claim 89, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

100. (Original) The method of claim 99, wherein the header compression key is included in a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the second field is a PDU type field.

101. (Original) The method of claim 89, wherein the header compression key is included in a protocol data unit of a link layer protocol.

102. (Cancelled)

103. (Cancelled)

104. (Cancelled)

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

105. (New) A telecommunications network having a first entity which communicates with a second entity by sending a packet having a compressed header, characterized in that the first entity also sends to the second entity a header compression key associated with the packet, the header compression key having a first field indicating a used header compression and packet type or context identifier, wherein a first subset of values for the first field of the header compression key is employed to distinguish between different header compression protocol packet types and wherein a second subset of values for the first field is employed to distinguish between the different contexts for a header compressed protocol.

106. (New) The apparatus of claim 105, wherein the values of the second subset succeed the values of the first subset.

107. (New) The apparatus of claim 105, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

108. (New) The apparatus of claim 107, wherein the header compression key is a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

109. (New) The apparatus of claim 105, wherein the second set of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

110. (New) The apparatus of claim 109, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

111. (New) A node of a cellular telecommunications network which has a first entity which communicates with a second entity by sending a packet having a compressed header, characterized in that the first entity also sends to the second entity a

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

header compression key associated with the packet, the header compression key having a first field indicating a used header compression and packet type or context identifier, wherein a first subset of values for the first field of the header compression key is employed to distinguish between different header compression protocol packet types and wherein a second subset of values for the first field is employed to distinguish between the different contexts for a header compressed protocol.

112. (New) The apparatus of claim 111, wherein the values of the second subset succeed the values of the first subset.

113. (New) The apparatus of claim 111, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

114. (New) The apparatus of claim 113, wherein the header compression key is a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

115. (New) The apparatus of claim 111, wherein the second set of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

116. (New) The apparatus of claim 115, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

117. (New) A user equipment unit (UE) having a first entity which communicates with a second entity by sending a packet having a compressed header, the second entity being situated at a node of a cellular telecommunications network, characterized in that the first entity also sends to the second entity a header compression key associated with the packet, the header compression key having a first field indicating a used header compression and packet type or context identifier, wherein a first subset of values for the first field of the header compression key is employed to distinguish between different

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

header compression protocol packet types and wherein a second subset of values for the first field is employed to distinguish between the different contexts for a header compressed protocol.

118. (New) The apparatus of claim 117, wherein the values of the second subset succeed the values of the first subset.

119. (New) The apparatus of claim 117, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

120. (New) The apparatus of claim 119, wherein the header compression key is a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

121. (New) The apparatus of claim 117, wherein the second set of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

122. (New) The apparatus of claim 121, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

123. (New) A method of operating a telecommunications network having a first entity which communicates with a second entity by sending a packet having a compressed header, the method characterized by sending from the first entity to the second entity a header compression key associated with the packet, the header compression key having a first field indicating a used header compression and packet type or context identifier, wherein a first subset of values for the first field of the header compression key is employed to distinguish between different header compression protocol packet types and wherein a second subset of values for the first field is employed to distinguish between the different contexts for a header compressed protocol.

SVANBRO et al
Serial No. 09/678,340

Atty Dkt: 2380-272
Art Unit: 2662

124. (New) The method of claim 123, wherein the values of the second subset succeed the values of the first subset.

125. (New) The method of claim 123, wherein the header compression key is included in a header of a protocol data unit of a link layer protocol.

126. (New) The method of claim 125, wherein the header compression key is a header of a protocol data unit for Packet Data Convergence Protocol (PDCP), and wherein the first field is a PID type field.

127. (New) The method of claim 123, wherein the second set of values comprise context identifiers for a compression/decompression algorithm which does not require packet type identification at a link layer level.

128. (New) The method of claim 127, wherein the compression/decompression algorithm is the Robust Header Compression (ROHC) algorithm.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.